



Tel: +44 (0)1767 681266

Email: info@sigatransformers.co.uk

Standard Toroidal Transformer Outputs

VA	Primary Volts	Secondary Volts	Secondary Current Amps	Dimensions mm (approx)	Regulation % (approx)	Weight Kg (approx)	Reference Number
----	---------------	-----------------	------------------------	------------------------	-----------------------	--------------------	------------------

30	2 x 120	2 x 6	2.50	65 Diameter 30 Height	17	0.39	S030-006
30	2 x 120	2 x 9	1.67		17	0.39	S030-009
30	2 x 120	2 x 12	1.25		17	0.39	S030-012
30	2 x 120	2 x 15	1.00		17	0.39	S030-015
30	2 x 120	2 x 18	0.83		17	0.39	S030-018
30	2 x 120	2 x 22	0.68		17	0.39	S030-022
30	2 x 120	2 x 25	0.60		17	0.39	S030-025
30	2 x 120	2 x 30	0.50		17	0.39	S030-030

60	2 x 120	2 x 9	3.33	78 Diameter 33 Height	14	0.62	S060-009
60	2 x 120	2 x 12	2.50		14	0.62	S060-012
60	2 x 120	2 x 15	2.00		14	0.62	S060-015
60	2 x 120	2 x 18	1.67		14	0.62	S060-018
60	2 x 120	2 x 22	1.36		14	0.62	S060-022
60	2 x 120	2 x 25	1.20		14	0.62	S060-025
60	2 x 120	2 x 30	1.00		14	0.62	S060-030

100	2 x 120	2 x 12	4.17	90 Diameter 37 Height	11	0.93	S100-012
100	2 x 120	2 x 15	3.33		11	0.93	S100-015
100	2 x 120	2 x 18	2.78		11	0.93	S100-018
100	2 x 120	2 x 22	2.27		11	0.93	S100-022
100	2 x 120	2 x 25	2.00		11	0.93	S100-025
100	2 x 120	2 x 30	1.67		11	0.93	S100-030
100	2 x 120	2 x 120	0.42		11	0.93	S100-120

160	2 x 120	2 x 12	6.67	99 Diameter 44 Height	9	1.45	S160-012
160	2 x 120	2 x 18	4.44		9	1.45	S160-018
160	2 x 120	2 x 22	3.64		9	1.45	S160-022
160	2 x 120	2 x 25	3.20		9	1.45	S160-025
160	2 x 120	2 x 30	2.67		9	1.45	S160-030

230	2 x 120	2 x 12	9.58	115 Diameter 45 Height	8	1.95	S230-012
230	2 x 120	2 x 18	6.39		8	1.95	S230-018
230	2 x 120	2 x 22	5.23		8	1.95	S230-022
230	2 x 120	2 x 25	4.60		8	1.95	S230-025
230	2 x 120	2 x 30	3.83		8	1.95	S230-030
230	2 x 120	2 x 120	0.96		8	1.95	S230-120

continued on next page...



Tel: +44 (0)1767 681266

Email: info@sigatransformers.co.uk

VA	Primary Volts	Secondary Volts	Secondary Current Amps	Dimensions mm (approx)	Regulation % (approx)	Weight Kg (approx)	Reference Number
330	2 x 120	2 x 25	6.60	126 Diameter	6.5	2.5	S330-025
330	2 x 120	2 x 30	5.50	45 Height	6.5	2.5	S330-030
330	2 x 120	2 x 35	4.71		6.5	2.5	S330-035
330	2 x 120	2 x 120	1.38		6.5	2.5	S330-0120

530	2 x 120	2 x 30	8.83	128 Diameter	5.5	4.2	S530-030
530	2 x 120	2 x 35	7.57	67 Height	5.5	4.2	S530-035
530	2 x 120	2 x 40	6.63		5.5	4.2	S530-040
530	2 x 120	2 x 45	5.89		5.5	4.2	S530-045
530	2 x 120	2 x 50	5.30		5.5	4.2	S530-050

Note - to comply with the requirements of UL506, the primary winding P1 & P2 must be connected either in series or parallel configuration. This requirement also applies to dual secondary where the related voltages are 15 volts and greater.